Windows Kernel Internals
User-mode Heap Manager

David B. Probert, Ph.D.

Windows Kernel Development

Microsoft Corporation

Topics

- Common problems with the NT heap
- LFH design
- Benchmarks data
- Heap analysis

Default NT Heap

- Unbounded fragmentation for the worst scenario:
  - External fragmentation
  - Virtual address fragmentation
- Poor performance for:
  - Large heaps
  - SMP
  - Large blocks
  - Fast growing scenarios
  - Fragmented heaps

Goals For LFH

- Bounded low fragmentation
- Low risk (minimal impact)
- Stable and high performance for:
  - Large heaps
  - Large blocks
 - SMP
  - Long running applications

LFH Design

- Bucket-oriented heap
- Better balance between internal and external fragmentation
- Improved data locality
- No locking for most common paths

Tradeoffs

- Performance / footprint
- Internal / external fragmentation
- Thread / processor data locality
- Using prefetch techniques

Block Size

0　　　　1K　　　　16 K　　　　512 K

LFH

NT Heap

NT Memory Manager

128
Buckets

8 | 16 • • • • • • • • • • • • 16 K

NT Heap

Allocation Granularity

Block Size	Granularity	Buckets
256	8	32
512	16	16
1024	32	16
2048	64	16
4096	128	16
8196	256	16
16384	512	16

128 Buckets

8   16   •••••••••••••   16 K

NT Heap

Active segment

User data area

Descriptor

Segment queue

Unmanaged segments

Alloc

Active segment

User data area

Descriptor

Segment queue

Unmanaged segments

Free

Active segment

Segment
queue

Unmanaged segments

Buckets

8   16   · · · · · · · · · · · · · ·   16 K

Large segments cache

Descriptors cache

Free

Active segment

Segment queue

Unmanaged segments

Buckets 8 16 .... 16 K

Large segments table

Descriptors cache

Improving the SMP Scalability

- Thread locality
- Processor locality

Thread Data Locality

- Advantages
  - Easy to implement (TLS)
  - Can reduce the number of interlocked instructions

- Disadvantages
  - Significantly larger footprint for high number of threads
  - Common source of leaks (the cleanup is not guaranteed)
  - Larger footprint for scenarios involving cross thread operations
  - Performance issues at low memory (larger footprint can cause paging)
  - Increases the CPU cost per thread creation / deletion

Processor Locality

- Advantages
  - The memory footprint is bounded to the number of CPUs regardless of the number of threads
  - Expands the structures only if needed
  - No cleanup issues

- Disadvantages
  - The current CPU is not available in user mode
  - Not efficient for a large number of processors and few threads

MP Scalability

8

16

16 K

Affinity manager

Data acceptor cache

Descriptors cache

System

Better Than Lookaside

- Better data locality (likely in same page)
- Almost perfect SMP scalability (no false sharing)
- Covers a larger size range (up to 16k blocks)
- Works well regardless of the number of blocks
- Non-blocking operations even during growing and shrinking phases

Benchmarks

- **Fragmentation**
- **Speed**
- **Scalability**
- **Memory efficiency**

Fragmentation
test for 266 MB limit

	Default	LFH
Uncommited	235 M**B**	39 MB
Free	4 MB	7 MB
Busy	26 MB	224 MB
Fragmentation	**88%**	**14%**

Default NT Heap

10%

2%

88%

Legend:
- Uncommited
- Free
- Busy

Low Fragmentation Heap

14%

3%

83%

- ■ Uncommited
- ■ Free
- ■ Busy

External Fragmentation Test (70 M**B**)

	Default	LFH
Uncommited	25 MB	7 MB
Free	32 MB	8 MB
Busy	12 MB	46 MB
Fragmentation	**46% + 36%**	**14% + 12%**

NT Heap at 70 M usage
(8478 UCR, 10828 free blocks)

18%

36%

46%

Uncommited

Free

Busy

Low Fragmentation Heap at 70 M
(417 UCR, 1666 free blocks)

Replacement test
0-1k, 10000 blocks (4P x 200MHz)

Replacement test
0-1k, 10000 blocks

**Replacement test
1-2k, 10000 blocks**

Replacement test on a 32P machine
0-1k, 100000 blocks

**Replacement test on 32P machine
0-1k, 100000 blocks**

Mem. Eff.

Threads (log)

LFH

NT

**Replacement test on 32P machine
22 bytes, 100000 blocks**

Replacement test on 32P machine
1k-2k, 100000 blocks

Threads (log)

Legend:
- LFH
- NT
- Ideal

Y-axis: Ops/sec (log) — 1000, 10000, 100000, 1000000, 10000000, 100000000

X-axis: 1, 2, 4, 8, 16, 32, 64, 128, 256, 512

Larson MT test on 32P machine
0 - 1k, 3000 blocks/thread

Larson MT test on 32P machine
0 - 1k, 3000 blocks/thread

Larson MT test on 32P machine
0 - 1k, 3000 blocks / thread

Larson MT test on 32P machine
1k -2k, 100000 blocks

Larson MT test on 32P machine
1k -2k, 100000 blocks

Aggressive alloc test on 32P machine
50 Mbytes allocs in blocks of 32 bytes

When is the Default Heap Preferred

- **~95% of applications**
- **The heap operations are rare**
- **Low memory usage**

Where LFH is Recommended

- High memory usage and:
  - High external fragmentation (> 10-15%)
  - High virtual address fragmentation (>10-15%)
- Performance degradation on long run
- High heap lock contention
- Aggressive usage of large blocks (> 1K)

Activating LFH

- **HeapSetInformation**
  - **Can be called any time after the heap creation**
  - **Restriction for some flags (HEAP_NO_SERIALIZE, debug flags)**
  - **Can be destroyed only with the entire heap**

- **HeapQueryInformation**
  - **Retrieve the current front end heap type**
    - **0 – none**
    - **1 – lookaside**
    - **2 – LFH**

Heap Analysis

- !heap to collect statistics and validate the heap
  - **!heap –s**
  - **!heap –s** *heap_addr* **–b***8*
  - **!heap –s** *heap_addr* **–d***40*
- Perfmon

Overall Heap Stats

```
0:001> !heap -s

  Heap       Flags     Reserv   Commit    Virt     Free   List    UCR   Virt   Lock  Fast
                        (k)      (k)       (k)      (k)   length        blocks cont. heap
-----------------------------------------------------------------------------------------------
00080000  00000002     1024       28       28       14      1      1      0      0    L
00180000  00008000       64        4        4        2      1      1      0      0
00250000  00001002       64       24       24        6      1      1      0      0    L
00270000  00001002   130304    58244    96888    36722  10828   8478      0      0    L
      External fragmentation   63 % (10828 free blocks)
      Virtual address fragmentation   39 % (8478 uncommited ranges)
-----------------------------------------------------------------------------------------------
```

Overall Heap Stats

```
0:000> !heap –s

  Heap        Flags      Reserv  Commit  Virt    Free  List    UCR  Virt  Lock  Fast
                          (k)      (k)    (k)     (k)  length       blocks cont. heap
-----------------------------------------------------------------------------------
00080000 00000002    1024      28      28      16     2       1     0       0
00180000 00008000      64       4       4       2     1       1     0       0
00250000 00001002      64      24      24       6     1       1     0       0
00270000 00001002     256     116     116       5     1       1     0       0
002b0000 00001002  130304  122972  122972    1936    67       1     0 14d5b8
      Lock contention  1365432
-----------------------------------------------------------------------------------
```

Overall Heap Stats

```
0:006> !heap -s

The process has the following heap extended settings 00000008:
    - Low Fragmentation Heap activated for all heaps

Affinity manager status:
    - Virtual affinity limit 8
    - Current entries in use 4
    - Statistics:  Swaps=18, Resets=0, Allocs=18
```

Heap	Flags	Reserv (k)	Commit (k)	Virt (k)	Free (k)	List length	UCR	Virt blocks	Lock cont.	Fast heap
00080000	00000002	1024	432	432	2	1	1	0	0	LFH
00180000	00008000	64	4	4	2	1	1	0	0	
00250000	00001002	1088	364	364	1	1	1	0	0	LFH
00370000	00001002	256	212	212	3	1	1	0	0	LFH
003b0000	00001002	7424	5720	6240	43	3	26	0	f	LFH

Default NT Heap Side

```
0:006> !heap -s 003b0000


Walking the heap 003b0000 ....
 0: Heap 003b0000
    Flags              00001002 - HEAP_GROWABLE
    Reserved        7424 (k)
    Commited        5720 (k)
    Virtual bytes   6240 (k)
    Free space      43 (k)
    External fragmentation             0% (3 free blocks)
    Virtual address fragmentation   8% (26 uncommited ranges)
    Virtual blocks  0
    Lock contention 15
    Segments        4
    2432 hash table for the free list
         Commits 0
         Decommitts 0
```

LFH Heap Side

```
Low fragmentation heap    003b0688
        Lock contention            4
        Metadata usage         76800
        Statistics:
            Segments created       2236
            Segments deleted        733
            Segments reused           0
            Conversions               0
            ConvertedSpace            0

        Block cache:
            Free blocks               0
            Sequence                  0
            Cache blocks      0     0    14    37    70    74    19
            Available         0     0    79   252   517   795    74
```

Default NT Heap Side

```
0:006> !heap -s 003b0000

Walking the heap 003b0000 ....
 0: Heap 003b0000
    Flags             00001002 - HEAP_GROWABLE
    Reserved          7424 (k)
    Commited          5720 (k)
    Virtual bytes  6240 (k)
    Free space        43 (k)
    External fragmentation            0% (3 free blocks)
    Virtual address fragmentation   8% (26 uncommited ranges)
    Virtual blocks  0
    Lock contention 15
    Segments          4
    2432 hash table for the free list
        Commits 0
        Decommitts 0
```

Blocks Distribution

Range (bytes)	Default heap Busy	Free	Front heap Busy	Free
0 - 1024	18	83	49997	9118
1024 - 2048	113	0	0	0
2048 - 3072	70	1	0	0
4096 - 5120	74	0	0	0
8192 - 9216	19	2	0	0
16384 - 17408	9	0	0	0
32768 - 33792	8	0	0	0
104448 - 105472	1	0	0	0
Total	312	86	49997	9118

Discussion